

# Carport



**FORM-TEC**

Part of **Gebhardt**Group



**SINGLE**



**SINGLE**



**ADD-ON**



**DOUBLE**



**DOUBLE**



**ADD-ON**

Clearance height	2.100 mm or 2.900 mm
Distance between supports	Single 2.508 mm Double: 5.580 mm Add-On: 5.860 mm
Locations	Industrial and commercial operations and private grounds
Variably expandable	With add-on elements
Roof	Anti-drip coating on trapezoidal sheet metal roof
Roof slope angle	5°
Foundation	Standard: Concrete base; Alternative: Ground anchors
Colour	Standard: Zinc Alternative: Powder coating: RAL 7016 anthracite, further options on request
Corrosion resistance	Zinc-magnesium coated quality steel that sets new standards, both in terms of technical properties as well as climate protection, sustainability and resource efficiency. This special metallic-chemical composition makes it almost impossible for environmental influences to penetrate, as the coating blocks corrosion processes
Wind load	Standard version with 7 purlins (cross bars) Basic velocity $v_{b,0} < 23,0$ m/s (DE = wind load zone 2)  Solid version 10 purlins (cross bars) Basic velocity $v_{b,0} < 27,5$ m/s (DE = wind load zone 3)
Snow load	Standard version with 7 purlins (cross bars) Snow load on the ground $s_k < 1,3$ kN/m <sup>2</sup>  Solid version 10 purlins (cross bars) Snow load on the ground $s_k < 2,58$ kN/m <sup>2</sup>